



FEATURES

- Enables the machine to be utilized for loading and stacking.
- Various fork length options available to reduce possible damage when stacking.
- Supplied with certification (lift governed by machine capability).

Part Number	531-70/ (T)	541-70T	535-140	550-140	550-170	531-70 Agri	536-60 Agri/ Plus	541-70 Agri Plus
328/00014			•	•				
328/00071			•	•				
328/00062				•				
328/00608					•			
328/00609					•			
328/00610					•			
328/00653	•	•	•	•	•	•		
328/00607					•			
160/12920					•			

Part Number	Style	Width	Fork Shaft	Fork Length	Fork Travel	Rotation (each side of center)	Swing (each side of center)	Capacity (lb)	Load Center
328/00014	Tilt	48"	2.25"			10°		10000	
328/00071	Tilt	66"	2.25"			10°		10000	
328/00062	Swing	72"	2.25"				50°	10000	
328/00608	Tilt	48"	2.25"			10°		8000	
328/00609	Tilt	66"	2.25"			10°		8000	
328/00610	Swing	72"	2.25"				50°	8000	
328/00653	Fork Positioning	60"		60" ITA	32"			10000	30"
328/00607	Framers	66"						8000	
160/12920	UK	48"						10000	

* Lifting capabilities refer solely to the attachment load capacity. Refer to machine spec sheets for machine lifting capabilities