



FEATURES

- Enables the machine to be utilized for loading and stacking.
- Various fork length options available to reduce possible damage when stacking.
- Supplied with certification (lift governed by machine capability).

Part Number	Fork Type	Capacity (lb)	Load Center	Size (in)	930	940
545/82136	Float	8400	24"	48x4x2	•	
547/08600	ITA	12800	20"	48x5x2	•	•
328/01091	ITA	10500	24"	72x5x2	•	•
330/00040	Float	8000	24"	60x4x2	•	
330/71754	Float	5000	24"	72x5x2	•	
330/71442	Black Tines	10100	24"	48x2x1.5	•	
545/82129	Float	10500	24"	48x5x2		•
330/71445	Float	10500	24"	60x5x2		•
330/71755	Float	6200	24"	72x5x2		•
330/71571	Float	12600	24"	48x2x2		•
328/01032	Fork Positioning	8000	24"	48	•	•
328/01038	Fork Positioning	8000	24"	60	•	•
328/01035	Fork Positioning	8000	24"	72	•	•

\* Lifting capacities refer solely to the attachment load capacity. Refer to machine spec sheets for machine lifting capabilities.

FL - Freelift  
 CV - CV  
 SS - Side Shifting  
 TPX - Triplex  
 DPX - Duplex