



JCB TRENCHER

The JCB Trencher is useful for trenching of footings, utilities burial, irrigations system installation, silt fence installation, and other job site applications.

| Part Number | Description | 160 | 170 | 180/180T | 190 / 190 T | 1110/1110T |
|-------------|--------------|-----|-----|----------|-------------|------------|
| 985/00022 | 36" Trencher | • | • | • | • | • |
| 985/00017 | 48" Trencher | | • | • | • | • |

FEATURES

- Equipped with two position side shift capabilities.
- Double standard 2" anti-back-flex chain for tooth pattern versatility.
- High torque hydraulic motor for maximum digging power and heavy duty chain reduction drive system to increase torque to the cutting chain.
- Maintenance free sealed idler bearing.
- Replaceable headshaft driven auger for spoil removal.
- Heavy duty wear strips on boom for longer life.
- Pivoting crumber shoe to assist with soil removal.

| Specifications | 36" Boom | 48" Boom |
|---|--------------------------------------|--------------------------------------|
| Weight | 1040lbs (472kg) | 1070lbs (485kg) |
| Trench Depth with auger @ 65 degree angle | 36in (914mm) | 48in (1219mm) |
| Headshaft Height | 8in (203mm) | 8in (203mm) |
| Overall Length | 73in (1854mm) | 85in (2159mm) |
| Overall Width | 53in (1346mm) | 53in (1346mm) |
| Overall Height | 32in (813) | 32in (813) |
| Spoil Discharge Reach | 18in (457) | 18in (457) |
| Side Shift, Right of Center | 17in (432mm) | 17in (432mm) |
| Hydraulic Requirements | 17in (432mm) | 17in (432mm) |
| Operating Pressure | 2000psi (138bar) to 3000psi (207bar) | 2000psi (138bar) to 3000psi (207bar) |
| Trenching Width | 8in (203mm) | 8in (203mm) |