FEATURES

- JCB general purpose buckets feature a rolled back shell for reduced spoil retention when emptying.
- A rolled top section gives maximum structural integrity.
- Optimum spacing of teeth gives maximum protection to the toeplate and improves penetration.
- Use of forged teeth and side cutters adds strength and durability to the corners, increasing the life of the bucket.
- Spring steel bushings prevent excessive wear to the bucket bosses.
- The addition of grease nipples enables regular lubrication to be carried out, further improving the working life of the bucket and pivot pins.

Part Number	Width	Capacity	8008	8018	804	8025	8030/ 8035	8040/ 8045	8052	8055	8060	8080
239/00187	6”	0.30 ft³	•									
239/00188	9”	0.61 ft³	•	•								
522/07400	6”	0.33 ft³		•								
522/00300	12”	0.86 ft³		•								
522/00500	16”	1.14 ft³		•								
522/01100	18”	1.47 ft³		•								
522/02100	9”	1.08 ft³			•		•					
522/02300	12”	1.61 ft³			•		•					
522/02500	18”	2.76 ft³			•		•					
522/02700	24”	3.89 ft³			•		•					
522/02900	30”	5.07 ft³			•		•					
980/90468	9”	0.83 ft³				•						
980/90470	12”	1.16 ft³				•						
980/90470	18”	1.91 ft³				•						
980/90471	24”	2.62 ft³				•						
980/90472	30”	3.33 ft³				•						
980/90185	9”	1.06 ft³						•		•		
980/90186	12”	1.77 ft³						•		•		
980/90187	18”	2.80 ft³						•		•		
980/90188	24”	3.50 ft³						•		•		
980/90189	30”	4.60 ft³						•		•		
980/89818	12”	2.25 ft³							•		•	•
980/89881	14”	2.50 ft³							•		•	•
980/89990	16”	3.00 ft³							•		•	•
980/89991	18”	3.60 ft³							•		•	•
980/89993	24”	5.20 ft³							•		•	•
528/04600	30”	6.90 ft³							•		•	
980/90178	36”	8.80 ft³							•		•	
980/89994	32”	8.48 ft³										•
980/89995	36”	9.89 ft³										•